





## Mesa

G-25001-J-M-I-C-6-036



### PENDANTS



|         | A       | B                                | C                                | D    | Weight |
|---------|---------|----------------------------------|----------------------------------|------|--------|
| G-25001 | in 24"  | 34"                              | 12 <sup>1</sup> / <sub>4</sub> " | 36"  | lbs 24 |
|         | mm 610  | 864                              | 305                              | 914  | kg 11  |
| G-25002 | A       | B                                | C                                | D    | Weight |
|         | in 30"  | 42 <sup>1</sup> / <sub>2</sub> " | 14 <sup>1</sup> / <sub>2</sub> " | 40"  | lbs 30 |
|         | mm 762  | 1080                             | 368                              | 1016 | kg 14  |
| G-25003 | A       | B                                | C                                | D    | Weight |
|         | in 36"  | 51"                              | 17 <sup>1</sup> / <sub>2</sub> " | 45"  | lbs 40 |
|         | mm 914  | 1295                             | 432                              | 1143 | kg 18  |
| G-25005 | A       | B                                | C                                | D    | Weight |
|         | in 48"  | 68"                              | 23 <sup>1</sup> / <sub>2</sub> " | 50"  | lbs 55 |
|         | mm 1219 | 1727                             | 572                              | 1270 | kg 25  |



### FLUSH MOUNTED



|         | A       | B                                | C                                | Weight |
|---------|---------|----------------------------------|----------------------------------|--------|
| G-25011 | in 24"  | 34"                              | 12 <sup>1</sup> / <sub>4</sub> " | lbs 19 |
|         | mm 610  | 864                              | 305                              | kg 9   |
| G-25012 | A       | B                                | C                                | Weight |
|         | in 30"  | 42 <sup>1</sup> / <sub>2</sub> " | 14 <sup>1</sup> / <sub>2</sub> " | lbs 27 |
|         | mm 762  | 1080                             | 368                              | kg 12  |
| G-25013 | A       | B                                | C                                | Weight |
|         | in 36"  | 51"                              | 17 <sup>1</sup> / <sub>2</sub> " | lbs 35 |
|         | mm 914  | 1295                             | 432                              | kg 16  |
| G-25015 | A       | B                                | C                                | Weight |
|         | in 48"  | 68"                              | 23 <sup>1</sup> / <sub>2</sub> " | lbs 51 |
|         | mm 1219 | 1727                             | 572                              | kg 23  |


## Lamping

| Incandescent  | Lumens | Lamp Base    | Code | Pendants |    |    |    | Flush Mounted |    |    |    |
|---|--------|--------------|------|----------|----|----|----|---------------|----|----|----|
|   |        |              |      | Diameter |    |    |    | Diameter      |    |    |    |
|   |        |              |      | 24       | 30 | 36 | 48 | 24            | 30 | 36 | 48 |
| 3-60 A-19   | 2,565  | Medium       | A    | •        | •  | •  | •  | •             | •  | •  | •  |
| 6-60 A-19   | 5,130  | Medium       | B    | •        | •  | •  | •  | •             | •  | •  | •  |
| 3-100 A-19  | 4,950  | Medium       | C    | •        | •  | •  | •  | •             | •  | •  | •  |
| 3-150 A-21  | 6,507  | Medium       | D    | •        | •  | •  | •  | •             | •  | •  | •  |
| 6-150 A-21  | 13,014 | Medium       | E    | •        | •  | •  | •  | •             | •  | •  | •  |
| 3-200 A-21  | 8,595  | Medium       | F    | •        | •  | •  | •  | •             | •  | •  | •  |
| 6-200 A-21  | 17,190 | Medium       | G    | •        | •  | •  | •  | •             | •  | •  | •  |
| <b>Fluorescent</b>  |        |              |      |          |    |    |    |               |    |    |    |
| 4 CFQ13   | 3,060  | G24q-1 4 Pin | H    | •        | •  | •  | •  | •             | •  | •  | •  |
| 4 CFQ26   | 5,840  | G24q-3 4 Pin | I    | •        | •  | •  | •  | •             | •  | •  | •  |
| 6 CFQ26   | 8,760  | G24q-3 4 Pin | J    | •        | •  | •  | •  | •             | •  | •  | •  |
| 8 CFQ26   | 11,680 | G24q-3 4 Pin | K    | •        | •  | •  | •  | •             | •  | •  | •  |
| 3-CF36/39   | 7,530  | 2G11 4 Pin   | L    | •        | •  | •  | •  | •             | •  | •  | •  |
| 4-CF36/39   | 10,040 | 2G11 4 Pin   | M    | •        | •  | •  | •  | •             | •  | •  | •  |
| 6-CF36/39   | 15,060 | 2G11 4 Pin   | N    | •        | •  | •  | •  | •             | •  | •  | •  |
| 9-CF36/39   | 22,590 | 2G11 4 Pin   | O    | •        | •  | •  | •  | •             | •  | •  | •  |
| CF36/39 lamp M.O.L. 16 1/2" long                            |        |              |      |          |    |    |    |               |    |    |    |
| <b>Metal Halide</b> Only available with hanger A, B, G or H |        |              |      |          |    |    |    |               |    |    |    |
| 1-175 ED-28   | 8,380  | Mogul        | P    | •        | •  | •  | •  | •             | •  | •  | •  |
| 1-250 ED-28   | 11,300 | Mogul        | Q    | •        | •  | •  | •  | •             | •  | •  | •  |
| 1-400 ED-28   | 22,700 | Mogul        | R    | •        | •  | •  | •  | •             | •  | •  | •  |

Please state voltage. See Code. Code: 1 120 volts  
2 277 volts

## Metal Halide

The reflector for our metal halide fixtures is finished with a highly reflective white powdercoat finish, which is also easy to maintain.



Ballasts are encased and potted, thermally protected with dual taps for 120 or 277 volts. Usually the ballast is mounted in a remote location. In the event this is not possible, the ballast may be mounted in specially designed, decorative traditional or contemporary canopies appropriate to the fixture style.

## Acrylic Lenses

|                | CODE |
|----------------|------|
| White Opal     | W    |
| Satin White    | S    |
| Faux Alabaster | F    |
| Earth Marble   | M    |

## Finishes

| Standard Painted Finishes | Code | Code                  |
|---------------------------|------|-----------------------|
| Satin Black               | A    | Light Bronze          |
| Reflector White           | B    | Dark Bronze           |
| Painted Aluminum          | C    | Painted Antique Brass |
| New Satin Nickel          | D    | Gray Granite          |
| Faux Rust                 | E    | Light Verde           |
| Beige                     | F    | Sungold               |

## Hangers

A Flat Ceiling  
B Sloped Ceiling  
C Flat Ceiling  
D Sloped Ceiling  
E Flat Ceiling  
F Sloped Ceiling  
G Flat Ceiling  
H Sloped Ceiling

For Sloped Ceilings

For lengths longer than 60" this method of hanging will be used with standard length stems


Custom lengths are available. Consult price sheet for added or shortened length.

## Options

All ballasts are high power factor electronic  
 Multi-circuiting is available. Consult factory for combinations and pricing.

### Code

- 1 Integral Dimming Ballasts
- 2 Emergency Ballasts-Available for fluorescent fixtures. Integral to operate 2 lamps in 36" Pyramids and above. All others remotely mounted. Only available with sloped ceiling hanger.
- 3 White Opal Top Lens (not available with Metal Halide)
- 3A Clear Top Lens (not available with Metal Halide)
- 4 150 Watt Quartz Restrike for Metal Halide (Only available with hanger A or B)
- 5 Surface Mounted Metal Halide Ballast Canopy



- 6 No Options Needed

Matching Fixtures: Contact factory.

## How To Specify

To specify a 48" diameter Mesa Pendant with 6-39 Watt Compact Fluorescent Lamping, 277 volts, Faux Alabaster Lens, Painted Antique Brass Finish, Triple Vertical Stem Hanger, Sloped Ceiling, Dimming Ballasts, Emergency Ballast, White Opal Top Lens, 52" Overall Length:

### G-25005-N2-F-I-D-123-052

