


Raider

G-15213-P1-W-A-G-6-038


PENDANTS

	A	B	C	D	E	Weight
G-15211	18"	25"	8"	29"	5½"	lbs 14
	457	635	203	737	140	kg 6
G-15212	24"	32"	9"	34"	6½"	lbs 17
	610	787	229	864	165	kg 8
G-15213	30"	39"	11"	38"	7½"	lbs 27
	762	991	279	965	192	kg 12
G-15214	38"	48"	12"	42"	9"	lbs 36
	965	1219	305	1067	229	kg 16



FLUSH MOUNTED

	A	B	C	Weight
G-15218	18"	25"	8"	lbs 9
	457	635	203	kg 4
G-15219	24"	32"	9"	lbs 11
	610	787	229	kg 5
G-15220	30"	39"	11"	lbs 19
	762	991	279	kg 9
G-15221	38"	48"	12"	lbs 23
	965	1219	305	kg 10




Lamping

	Incandescent	Lumens	Lamp Base	Code	Pendants				Flush Mounted			
					Bowl Diameter				Bowl Diameter			
					18	24	30	38	18	24	30	38
	3-60 A-19	2,565	Medium	A	•	•	•	•	•	•	•	•
	6-60 A-19	5,130	Medium	B	•	•	•	•	•	•	•	•
	3-100 A-19	4,950	Medium	C	•	•	•	•	•	•	•	•
	6-100 A-19	9,900	Medium	D	•	•	•	•	•	•	•	•
	3-150 A-21	6,507	Medium	E	•	•	•	•	•	•	•	•
	6-150 A-21	13,014	Medium	F	•	•	•	•	•	•	•	•
	3-200 A-21	8,595	Medium	G	•	•	•	•	•	•	•	•
	6-200 A-21	17,190	Medium	H	•	•	•	•	•	•	•	•
	3-300 PS30	18,300	Medium	I	•	•	•	•	•	•	•	•
	6-300 PS30	36,600	Medium	J	•	•	•	•	•	•	•	•
Fluorescent												
	2 CFQ13	1,530	G24q-1 4 Pin	K	•	•	•	•	•	•	•	•
	4 CFQ13	3,060	G24q-1 4 Pin	L	•	•	•	•	•	•	•	•
	4 CFQ26	5,840	G24q-3 4 Pin	M	•	•	•	•	•	•	•	•
	8 CFQ26	11,680	G24q-3 4 Pin	N	•	•	•	•	•	•	•	•
	3-CF36/39	7,530	2G11 4 Pin	O	•	•	•	•	•	•	•	•
	4-CF36/39	10,040	2G11 4 Pin	P	•	•	•	•	•	•	•	•
	6-CF36/39	15,060	2G11 4 Pin	Q	•	•	•	•	•	•	•	•
	9-CF36/39	22,590	2G11 4 Pin	R	•	•	•	•	•	•	•	•
	8-CF50	27,200	2G11 4 Pin	S	•	•	•	•	•	•	•	•
	10-CF50	34,000	2G11 4 Pin	T	•	•	•	•	•	•	•	•
	CF36/39 lamp M.O.L. 16 1/2" long											
Metal Halide Only available with hanger A, B, C, D, G or H												
	1-175 ED-28	8,380	Mogul	U	•	•	•	•	•	•	•	•
	1-250 ED-28	11,300	Mogul	V	•	•	•	•	•	•	•	•
	1-400 ED-28	22,700	Mogul	W	•	•	•	•	•	•	•	•
Please state voltage. See Code.		Code: 1 120 volts 2 277 volts										

Metal Halide

The reflector for our metal halide fixtures is finished with a highly reflective white powdercoat finish, which is also easy to maintain.



Ballasts are encased and potted, thermally protected with dual taps for 120 or 277 volts. Usually the ballast is mounted in a remote location. In the event this is not possible, the ballast may be mounted in specially designed, decorative traditional or contemporary canopies appropriate to the fixture style.

Acrylic Bowls

	CODE		CODE
White Opal	W	Satin White	S
Faux Alabaster	F	Earth Marble	M

Finishes

Standard Finishes	Code	Special Finishes	Code
Satin Black	A	Contact factory for price and availability	B
Brushed Aluminum			
Polished Brass			

Hangers

A Flat Ceiling
 B Sloped Ceiling
 C Flat Ceiling
 D Sloped Ceiling
 E Flat Ceiling
 F Sloped Ceiling
 G Flat Ceiling
 H Sloped Ceiling

For Sloped Ceilings

For lengths longer than 60" this method of hanging will be used with standard length stems


Custom lengths are available. Consult price sheet for added or shortened length.

Options

All ballasts are high power factor electronic
 Multi-circuiting is available. Consult factory for combinations and pricing.

Code

- 1 Integral Dimming Ballasts
- 2 Emergency Ballasts-Available for fluorescent fixtures. Integral to operate 2 lamps in 30" bowls and above. All others remotely mounted. Only available with sloped ceiling hanger.
- 3 White Opal Top Lens (not available with Metal Halide)
- 3A Clear Top Lens (not available with Metal Halide)
- 4 150 Watt Quartz Restrike for Metal Halide -Contact factory. Special hanger required.
- 5 Surface Mounted Metal Halide Ballast Canopy



- 6 No Options Needed

Matching Fixtures: Contact Factory

How To Specify

To specify a 30" diameter bowl Raider Pendant with 6-150 Watt Incandescent Lamping, 120 volts, White Opal Bowl, Standard Finish, Cable Hangers, Sloped Ceiling, Top Lens, 38" Overall Length:

G15213-F1-W-A-B-3-038

Fixture No. _____

Lamping, Voltage _____

Bowl _____

Finish _____

Hanger _____

Options _____

Overall Length _____